

EC CERTIFICATE

CERTIFICATE OF CONSTANCY OF PERFORMANCE CERTIFICATE No. 2821-CPR-0193

In compliance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product and placed on the market under the name or trademark of

Manufacturer: FireSeal AB

Address: Esbogatan 14

164 07 Kista Sweden

Product: Squeezer L, pipe closure device

Places of production: A/005

Harmonized EAD 350454-00-1104, edition September 2017

requirements:

Scope of certificate:

ETA 21/0194, issued on 23/04/2021

Product area code: 35, Fire stopping, fire sealing and fire protective products

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in the ETA 21/0194 and EAD 350454-00-1104 under system 1 (or 1+) for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 07/02/2022 and will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The validity of the certificate may be confirmed by contacting UL International (NL) B.V. via e-mail address <u>info.nl@ul.com</u>

Revision: 0
Date of revision: N/A

Issued by UL International (NL) B.V. Notified Body 2821.

Signed:

Name: Horst Thelen

Head of Notified Body



EC CERTIFICATE

Schedule for certificate No. 2821-CPR-0193

General Information

Product Reference: Squeezer L

Type: Firestop – Pipe closure device used as a penetration seal Description: A pipe closure device used to form penetration seals where

combustible pipes, cables and metal pipes with insulation

penetrate walls and floors. See ETA 21/0194

Key Performance

parameters:

Identification and intended

use

The Squeezer L is supplied with intumescent liner complete within metal steel shell, to be clamped around the service and screw fixed back to the supporting element. The Squeezer L may be supplied with powder coated steel shells incorporating a hinge and toggle latch, stainless steel half shells with slide together fixing and galvanized steel half shells with slide

together fixing.

CE marking method Label on the product

UL Project: 4790120786

Limitations on the acceptance or use of the product(s):

Installation instructions To be used in accordance with the supplier's installation

instructions, the Technical Data Sheet and the ETA.

Limitations See Technical Data Sheet and the ETA

Terms and Conditions:

- 1. This certificate remains the property of UL International (NL) B.V, herein "UL NL", and will be withdrawn if any conditions attached to its issue are not complied with.
- 2. This certificate is issued subject to the Global Services Agreement (GSA) and CPR Service Terms.
- 3. Production is limited to the site(s) as listed, or detailed within the Technical documentation held by UL NL.
- 4. Any product change, production/process changes, etc. which may affect conformity shall be notified to UL NL.
- 5. This certificate is only valid for placing goods on the EU market.
- 6. The requirements for the economic operators stipulated in CHAPTER II, Article 4 of the Regulation (EU) 2019/1020 of the European Parliament and of the Council of 20 June 2019

END OF CERTIFICATE

Revision: 0
Date of revision: N/A

Issued by UL International (NL) B.V. Notified Body 2821.

Signed:

Name: Horst Thelen

Head of Notified Body

Page 2 of 2